



► STAINLESS STEEL / EDELSTAHL

DESCRIPTION / BESCHREIBUNG	MMA-2525095-AX		MMA-2828095-AX		MMA-3028095-AX		MMA-3434095-AX		MMA-3826095-AX		MMA-4035155-AX	
VERSION	1	2	1	2	1	2	1	2	1	2	1	2
OUTER DIAMETER mm	25.0 ± 0.5	25.0 ± 0.5	28.0 ± 0.5	28.0 ± 0.5	30.0 ± 0.5	30.0 ± 0.5	34.0 ± 0.5	34.0 ± 0.5	38.5 ± 0.5	38.5 ± 0.5	40.0 ± 0.5	40.0 ± 0.5
HEIGHT mm	24.5 ± 0.5	24.5 ± 0.5	28.5 ± 0.5	28.5 ± 0.5	28.0 ± 0.5	28.0 ± 0.5	34.5 ± 0.5	34.5 ± 0.5	26.5 ± 0.5	26.5 ± 0.5	36.0 ± 0.5	36.0 ± 0.5
INNER DIAMETER mm	9.5 ± 0.3	9.5 ± 0.3	9.5 ± 0.3	9.5 ± 0.3	9.5 ± 0.5	9.5 ± 0.5	9.5 ± 0.3	9.5 ± 0.3	9.5 ± 0.3	9.5 ± 0.3	15.5 ± 0.3	15.5 ± 0.3
WEIGHT g	6.0 ± 0.3	6.0 ± 0.3	8.0 ± 0.3	8.0 ± 0.3	7.0 ± 0.5	7.0 ± 0.5	11.5 ± 1.0	11.5 ± 1.0	11.0 ± 1.0	11.0 ± 1.0	21.0 ± 1.0	21.0 ± 1.0
DENSITY OF FLOAT g/cm ³	0.80	0.80	0.75	0.75	0.70	0.70	0.70	0.70	0.70	0.70	0.65	0.65
MATERIAL	SUS304	SUS316L	SUS304	SUS316L	SUS304	SUS316L	SUS304	SUS316L	SUS304	SUS316L	SUS304	SUS316L



DESCRIPTION / BESCHREIBUNG	MMA-4050155-AX		MMA-4242115-AX		MMA-4556155-AX		MMA-5252155-AX		MMA-5262155-AX	
VERSION	1	2	1	2	1	2	1	2	1	2
OUTER DIAMETER mm	40.2 ± 0.5	40.2 ± 0.5	42.0 ± 0.5	42.0 ± 0.5	45.2 ± 0.5	45.2 ± 0.5	52.0 ± 0.5	52.0 ± 0.5	52.0 ± 0.5	52.0 ± 0.5
HEIGHT mm	51.0 ± 0.5	51.0 ± 0.5	41.5 ± 0.5	41.5 ± 0.5	56.0 ± 1.0	56.0 ± 1.0	52.0 ± 1.0	52.0 ± 1.0	62.5 ± 1.0	62.5 ± 1.0
INNER DIAMETER mm	15.5 ± 0.3	15.5 ± 0.3	11.5 ± 0.5	11.5 ± 0.5	15.5 ± 0.5	15.5 ± 0.5	15.5 ± 0.5	15.5 ± 0.5	15.5 ± 0.5	15.5 ± 0.5
WEIGHT g	30.0 ± 2.0	30.0 ± 2.0	16.5 ± 1.0	16.5 ± 1.0	39.0 ± 2.0	39.0 ± 2.0	32.5 ± 1.0	32.5 ± 1.0	49.0 ± 2.0	49.0 ± 2.0
DENSITY OF FLOAT g/cm ³	0.75	0.75	0.65	0.65	0.70	0.70	0.70	0.70	0.68	0.68
MATERIAL	SUS304	SUS316L	SUS304	SUS316L	SUS304	SUS316L	SUS304	SUS316L	SUS304	SUS316L

